



Enduris™ Bitumen Bleed Blocker

The foundation for a smooth finish.

Prevent unsightly bleed-through and bitumen staining with Enduris Bitumen Bleed Blocker.

Enduris Bitumen Bleed Blocker is part of the complete Enduris Roof Coating system. Applied as a base coat to asphaltic and bitumenous substrates and surfaces, it is formulated to seal out oils that can discolor the finished coat, helping to protect your investment.

Enduris Bitumen Bleed Blocker is a long lasting, breathable, and flexible barrier coating that prevents bleed through from bitumenic substrates and bitumen-based surfaces such as BUR, modified bitumen, and bitumen cap sheet. It's the first step to an even coloured and lasting finish on your next roofing project.



Key Features of Enduris Bitumen Bleed Blocker

Bleed Resistant.

Formulated with special materials to block the bleed-through of bitumen components that can discolor topcoats.

Exceptional Adhesion.

Exceptional adhesion to bitumen and other surfaces including metal, most single-ply roofs, wood, and concrete. Chemically and adhesively compatible with Enduris roof coatings and accessory products.

Easy to use.

This single component, water-based acrylic elastomer basecoat can be applied with spray, brush, or roller. The color is light yellow as installed and darkens as it cures, allowing enhanced visual confirmation for application of the basecoat. The coating cures quickly, becoming rain-ready within hours.

Breathability.

Enduris Bitumen Bleed Blocker basecoat is part of a breathable coating system that allows trapped moisture to escape.

This can make a real difference to the internal temperature and comfort of the building – and can result in energy savings and reduced carbon emissions from HVAC system usage.



Ready to start your next project?
[gesilicones.com](https://www.gesilicones.com)

THE MATERIALS, PRODUCTS, AND SERVICES OF MOMENTIVE PERFORMANCE MATERIALS INC. AND ITS SUBSIDIARIES AND AFFILIATES (COLLECTIVELY "SUPPLIER"), ARE SOLD SUBJECT TO SUPPLIER'S STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT, PRINTED ON THE BACK OF ORDER ACKNOWLEDGMENTS AND INVOICES, AND AVAILABLE UPON REQUEST. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SUPPLIER MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING ITS PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS, OR ADVICE, EXCEPT AS PROVIDED IN SUPPLIER'S STANDARD CONDITIONS OF SALE, SUPPLIER AND ITS REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS, OR SERVICES DESCRIBED HEREIN. Each user bears full responsibility for making its own determination as to the suitability of Supplier's materials, services, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished parts incorporating Supplier's products, materials, or services will be safe and suitable for or waive any provision of Supplier's standard Conditions of Sale or this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Supplier. No statement contained herein concerning a possible or suggested use of any material, product, service, or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Supplier covering such use or design, or as a recommendation for the use of such material, product, service, or design in the infringement of any patent or other intellectual property right.

GE is a trademark of General Electric Company. Used under trademark license.
The use of the "™" symbol designates registered or unregistered trademarks of Momentive Performance Materials Inc. or its affiliated companies.
Copyright 2022 Momentive Performance Materials Inc. All rights reserved.